



CanoScan LiDE400

- Superior scanner with exceptional speed quality and style
- USB-C connectivity
- 5 EZ Buttons for fast operation
- Space saving design with upright scanning option
- Scan bulky documents up to 21mm thick with Z-lid hinge

no one sees it like you

Canon



TECHNICAL SPECIFICATIONS – CANOSCAN LiDE400

| | | |
|--|--------------------------|---|
| Scanner Type | | Flatbed |
| Scanner Element | | CIS |
| Light Source | | 3-color (RGB) LED |
| Optical Resolution* ¹ | | 4800 x 4800dpi |
| Selectable Resolution* ² | | 25 - 19200 dpi |
| Scanning Bit Depth | Grayscale | 16 bit input 8 bit output |
| | Color | 48 bit input (16 bit for each color) Win:「48 or 24 bit output(16 bit or 8 bit for each color)」 Mac:「24 bit output(8 bit for each color)」 *48bit :Windows TWAIN Driver only |
| Preview Speed* ³ | | Approx. 7 sec |
| Scan Speed* ⁴ | Color A4 300dpi | Approx. 8 sec |
| | Color 4"x6" 300dpi | Approx. 4 sec |
| Scanning Speed* ⁵ (Reflective) | Grayscale, B&W | 8.2msec/line (4800 dpi) 4.3msec/line (2400 dpi) 2.2msec/line (1200 dpi) 1.3msec/line (600 dpi) 1.7msec/line (300 dpi) |
| | Color | 25.4msec/line (4800 dpi) 14.8msec/line (2400 dpi) 6.6msec/line (1200 dpi) 3.8msec/line (600 dpi) 1.7msec/line (300 dpi) |
| Scanning Speed* ⁵ (Film) | Color, Grayscale, B&W | N/A |
| Maximum Document Size | | A4/LTR |
| Film Type/No. of frames | | NO |
| Scanner Buttons (EZ buttons) | | 5 buttons (PDF x 2, AUTOSCAN, COPY, SEND) |
| Interface | | USB2.0 High-Speed Type-C |
| Operating Environment | Temperature | 5 - 35°C (41 - 95°F) |
| | Humidity | 10 - 90%RH (no dew condensation) |
| Power Supply | | Supplied via USB port |
| Power Consumption | Maximum during operation | approx. 4.5W |
| | Stand-by | approx. 0.3W |
| Dimension(WxDxH) | mm | 250×367×42 mm |
| Weight | kg | 1.7 |

*1 Optical resolution is a measure of maximum hardware sampling resolution, based on ISO 14473 standard.

*2 Increasing the scanning resolution will limit the maximum possible scanning area.

*3 Preprocessing time is not included.

*4 Connecting the bundled USB cable to the port corresponding to USB3.0 and above on PC. Color document scan speed:(Color A4 300dpi) is measured with ISO/IEC 29183 Target-A. Color photo scan speed:(4"x6" 300dpi) is measured with ISO/JIS SCID No.2. Scan speed indicates the time measured between pressing the scan button of the scanner driver and the on-screen status display turns off. Scan speed may vary depending on system configuration, interface, software, scan mode settings and document size etc.

*5 The fastest speed in Hi-Speed USB on Windows PC. Transfer time to computer is not included.

Specifications are subject to change without notice.

no one sees it like you

Canon