

Part No **42817**

## 5M USB 2.0 ACTIVE EXTENSION SLIM

**5M USB 2.0 EXTENSION OF A USB TYPE A PORT OF YOUR COMPUTER**

### DESCRIPTION

- 5 metre USB 2.0 Active Extension Repeater Lead
- Supports transfer rates up to 480Mbps
- For even greater distances simply connect up to 5 cables in series
- Plug & Play
- 2 year warranty

The Lindy USB 2.0 Active Extension Cable Slim uses built-in active electronics to extend the cable length of a USB 2.0 device by an additional 5m whilst continuing to support data transfer rates of up to 480Mbps. With its USB A male and USB A female connector it allows Type A devices to be connected at longer distances and ensures flexible positioning. Up to 5 extension cables can be chained together to achieve a distance of 25m.

The cable's unique and slim design allows the active electronics to fit into a standard USB connector - an advantage over other active USB leads which use bulky connectors. Compatible with all USB Type A equipped computers.

### RELATED PRODUCTS

N/A

# 5M USB 2.0 ACTIVE EXTENSION SLIM

## CONNECTORS

<b>Connector A</b>	USB Type A Male
<b>Connector B</b>	USB Type A Female
<b>Power</b>	-
<b>Housing Material</b>	Plastic
<b>Connector Plating</b>	Nickel
<b>Pin Construction</b>	Brass
<b>Pin Plating</b>	Gold
<b>Dimensions (approx.) WxDxH</b>	USB A Male: 15x40x6mm [0.59x1.57x0.24in] USB A Female: 15x45x8mm [0.59x1.77x0.31in]

## SPECIFICATONS

<b>Supported Bandwidth</b>	480 Mbps
<b>Nominal Attenuation</b>	24AWG: 93.250hm/km 28AWG: 237.250hm/km

<b>Minimum Bend Radius</b>	48mm [1.89in]
<b>Maximum Tensile Load</b>	-
<b>Operating Temperature</b>	0°C - 70°C [32°F - 158°F]
<b>Storage Temperature</b>	-10°C - 80°C [14°F - 176°F]
<b>Transmission Medium</b>	Twisted Pair
<b>Transmission Technology</b>	USB 2.0

## PURCHASING INFORMATION

<b>No.</b>	42817
<b>EAN</b>	4002888428170

## CABLE CONSTRUCTION

<b>Length</b>	5m [16.4ft]
<b>Standard</b>	USB 2.0
<b>Colour</b>	Black
<b>Type</b>	Round
<b>Jacket Diameter</b>	4.8mm [0.19in]
<b>Jacket Material</b>	PVC
<b>Conductor Material</b>	Tinned Copper
<b>Conductor Gauge</b>	24AWG+28AWG
<b>Shielding</b>	AL Mylar

## MISCELLANEOUS

<b>Packaging Type</b>	Blister
<b>Packaging Dimensions</b>	214x146x38mm [8.43x5.75x1.5in]
<b>Net Weight</b>	0.18kg [0.4lb]
<b>Gross Weight</b>	0.2kg [0.48lb]
<b>Warranty (Years)</b>	2
<b>Certificated</b>	CE, FCC, RoHS & REACH

## AVAILABLE IN OTHER LENGTHS

42630 - 10m [32.8ft] with hub  
42631 - 20m [65.62ft]

## THIS PRODUCT IS ALSO AVAILABLE IN OTHER LENGTHS

42630 - 10m [32.8ft] with hub 4263