

Part No. **43229**

## 15M USB 3.0 ACTIVE EXTENSION PRO

**EXTEND USB 3.0 CONNECTIONS UP TO 40M**

### DESCRIPTION

High performance, active cable that provides an extended 15m connection between a computer and USB 3.0 device  
Can be used standalone or as part of the Lindy Active Extension System Pro to create bespoke extension systems of over 40m  
(depending on the cable configurations used)  
Supports the full USB 3.0 SuperSpeed bandwidth for speeds of 5Gbps  
Easy to use – connects to the device's existing USB cable (5m maximum)  
2 year warranty

The Lindy USB Active Extension Cable Pro is a high performance active cable that allows access to USB 3.0 SuperSpeed peripherals over long distances. With support for data transfer speeds of up to 5Gbps this extension cable is perfect for transferring large data volumes quickly and reliably.

This 15m extension cable can be used standalone or as part of the Lindy USB 3.0 Active Extension System Pro. This system is a modular solution that can combine multiple USB Active Extension Pro cables and a USB 3.0 Active Extension Pro hub to distribute USB signals to up to 4 devices at up to 50m (depending on the cable configurations used).

The 8m and 10m cable, and the 10m hub, feature a single active repeater module to boost the USB signal. The 15m cable uses two repeaters. A fully deployed extension system is limited to a maximum of 50m and 5 repeater modules. Any combination of cables and a single hub can be connected providing the 50m / 5 repeater limit is not exceeded. The extension hub must always be the last segment of the extension system.

This cable features industry-proven active technology and locking connectors to ensure full signal integrity in the most demanding environments.

### RELATED PRODUCTS

N/A

# 15M USB 3.0 ACTIVE EXTENSION PRO

## CONNECTORS

<b>Connector A</b>	USB Type A Male
<b>Connector B</b>	USB Type A Female
<b>Power</b>	2.5/0.7mm DC Connector
<b>Housing Material</b>	Plastic
<b>Connector Plating</b>	Nickel
<b>Pin Construction</b>	Brass
<b>Pin Plating</b>	Gold Flash
<b>Dimensions (approx.) WxDxH</b>	USB A Male: 15x49x8mm [0.59x1.93x0.31in] USB A Female: 20x80x13mm [0.79x3.15x0.51in]

## SPECIFICATONS

<b>Supported Bandwidth</b>	5 Gbps
<b>Nominal Attenuation</b>	0.064MHz - <0.08dB 0.256MHz - <0.11dB 0.512MHz - <0.13dB 0.772MHz - <0.15dB 1.0MHz - <0.20dB 4MHz - <0.39dB 8MHz - <0.57dB 12MHz - <0.67dB 24MHz - <0.95dB 48MHz - <1.35dB 96MHz - <1.90dB 200MHz - <3.20dB 400MHz - <5.80dB
<b>Minimum Bend Radius</b>	36mm [1.42in]
<b>Maximum Tensile Load</b>	-
<b>Operating Temperature</b>	0°C - 50°C [32°F - 122°F]
<b>Storage Temperature</b>	-20°C - 60°C [-4°F - 140°F]
<b>Transmission Medium</b>	Twisted Pair
<b>Transmission Technology</b>	USB 3.1 Gen 1 / 3.0

## PURCHASING INFORMATION

<b>No.</b>	43229
<b>EAN</b>	4002888432290

## CABLE CONSTRUCTION

<b>Length</b>	15m [49.21ft]
<b>Standard</b>	USB 3.1 Gen 1 / 3.0
<b>Colour</b>	Black
<b>Type</b>	Round
<b>Jacket Diameter</b>	7mm +/- 0.15mm [0.28in +/- 0.01in]
<b>Jacket Material</b>	Half matt PVC low toxic
<b>Conductor Material</b>	Tinned Copper
<b>Conductor Gauge</b>	24/24/20AWG
<b>Shielding</b>	AL Mylar and braid

## MISCELLANEOUS

<b>Packaging Type</b>	Carton Box
<b>Packaging Dimensions</b>	280x180x10mm [11.02x7.09x0.39in]
<b>Net Weight</b>	1kg [2.2lb]
<b>Gross Weight</b>	1.351kg [2.98lb]
<b>Warranty (Years)</b>	2
<b>Certificated</b>	CE, FCC, RoHS, REACH & California Proposition 65

## AVAILABLE IN OTHER LENGTHS

43158 - 8m [26.25ft]
43157 - 10m [32.81ft]

## THIS PRODUCT IS ALSO AVAILABLE IN OTHER LENGTHS

43158 - 8m [26.25ft]
----------------------